

SOUSTRUHY

CNC SOUSTRUHY SE ŠIKMÝM LOŽEM



CNC SOUSTRUHY SE ŠIKMÝM LOŽEM		KL 285	KL 285 MC	KL 285 Y	KL 285 SMC	KL 285 SY
Oběžný průměr nad ložem	(mm)	670	670	670	670	670
Max. průměr soustružení	(mm)	340	340	340	304	304
Max. délka soustružení	(mm)	550	550	550	---	---
Max. zdvih v ose X / Z	(mm)	243 × 610	243 × 610	243 × 610	168 × 610	168 × 610
Otáčky vřetena	(min ⁻¹)	5000	5000	5000	5000	5000
Nástrojová hlava - počet poloh	-	12	12	12	12	12



CNC SOUSTRUHY SE ŠIKMÝM LOŽEM		KL 435	KL 435MC	KL 435Y
Oběžný průměr nad ložem	(mm)	700	700	700
Max. průměr soustružení	(mm)	550	550	550
Max. délka soustružení	(mm)	1100	1100	1100
Max. zdvih v ose X / Z	(mm)	345 × 1225	345 × 1225	325 × 1225
Otáčky vřetena	(min ⁻¹)	3800	3800	3800
Nástrojová hlava - počet poloh	-	12	12	12